

APPENDIX A

fs_purge.script

```
isql -Usa -Pjc4251 -e <<!  
use faultdb1  
go
```

```
drop proc fs_purgen  
go
```

```
/*  
** Create the PURGE stored procedure  
***/
```

```
CREATE procedure fs_purgen  
(  
    @db_name varchar(30),  
    @segment_name varchar(30),  
    @space_left int,  
    @status int  
)  
as
```

```
/*  
** purge procedure will now run every hour to avoid LONG  
** lockups at midnight. Just in case we have an extremely busy  
** hour, limit row count to 45k (15 traps/sec) to avoid running out  
** of locks  
***/
```

```
    set rowcount 1500000  
    DECLARE @activeAlarmRetainDays int  
    DECLARE @closedAlarmRetainDays int  
    DECLARE @dateStamp varchar(40)
```

```
    SELECT @activeAlarmRetainDays = (SELECT ActiveAlarmRetainDays  
    FROM FaultServerConfig)
```

```
    SELECT @closedAlarmRetainDays = (SELECT ClosedAlarmRetainDays  
    FROM FaultServerConfig)
```

```
    SELECT @dateStamp = (getdate())
```

```
    SET transaction isolation level 0  
    PRINT "Purge started ...      (%!)", @dateStamp  
    PRINT "Purging old opentrap ... (%!)", @dateStamp
```

```
    BEGIN tran  
        DECLARE @CustomerID binary(4)  
        SELECT @CustomerID = 0  
  
        DECLARE openPurgeAlarmKeyCur cursor FOR  
        SELECT AlarmKey FROM OpenAlarm WHERE  
        TimeStamp < dateadd(day, -@activeAlarmRetainDays, getdate())  
  
        OPEN openPurgeAlarmKeyCur  
  
        DECLARE @tempAlarmKey numeric(30, 0)
```

```

    FETCH openPurgeAlarmKeyCur into @tempAlarmKey
    WHILE (@@sqlstatus = 0)
    BEGIN
        UPDATE Alarm
        SET ActiveBit = 0
        WHERE AlarmKey = @tempAlarmKey
        DECLARE @RowKey_bin binary(4)
        SELECT @RowKey_bin = convert(binary(4),convert(int,@tempAlarmKey))
        EXEC DBAction_insert 'OpenAlarm', 'D', @RowKey_bin, @CustomerID

        FETCH openPurgeAlarmKeyCur into @tempAlarmKey
    END

    CLOSE openPurgeAlarmKeyCur
    DEALLOCATE cursor openPurgeAlarmKeyCur
    delete OpenTrap where TrapKey not in (select TrapKey from OpenEvent)
    COMMIT tran

    SET transaction isolation level 1

/*****
** delete closed alarms that are older than the closedAlarmRetainDays and
** the corresponding Events, GroupAlarms and Traps
*****/

    SELECT @dateStamp = (getdate())

    PRINT "Purging old closed alarms ...      (%!)", @dateStamp

    BEGIN tran
        DELETE Alarm from Alarm a WHERE
            TimeStamp < dateadd(day, -@closedAlarmRetainDays, getdate()) AND
            ActiveBit = 0
    COMMIT tran

/*****
** delete all corresponding Events,GroupAlarms and Traps
*****/

    SELECT @dateStamp = (getdate())
    PRINT "Purging old group alarms ...      (%!)", @dateStamp

    BEGIN tran
        DELETE GroupAlarm WHERE
            GroupAlarmKey not in (SELECT AlarmKey FROM Alarm)
    COMMIT tran

    SELECT @dateStamp = (getdate())
    PRINT "Purging old events ...            (%!)", @dateStamp

    BEGIN tran
        DELETE Event FROM Trap t, Event e WHERE
            e.TrapKey = t.TrapKey AND
            t.TimeStamp < dateadd(day, -@closedAlarmRetainDays, getdate()) AND
            e.EventKey not in (SELECT EventKey FROM Alarm) AND
            e.EventKey not in (SELECT EventKey FROM GroupAlarm)
    COMMIT tran

    SELECT @dateStamp = (getdate())

```

```

PRINT "Purging old traps ...          (%!)", @dateStamp

BEGIN tran
    DELETE Trap WHERE TrapKey not in (SELECT TrapKey FROM Event) AND
        TimeStamp < dateadd(day, -@closedAlarmRetainDays, getdate())
COMMIT tran

SELECT @dateStamp = (getdate())
PRINT "Purging old CircuitAlarms ...  (%!)", @dateStamp

DELETE CircuitAlarm WHERE datediff(day,TimeStamp,getdate())
    > (select  MaxCircuitAlarmDays from FaultServerConfig)
/*****
**      MaxCircuitAlarmDays is used for SLA reports
**      > @closedAlarmRetainDays
*****/
SELECT @dateStamp = (getdate())
PRINT "Purge completed ...          (%!)", @dateStamp

go
!
```

APPENDIX B

fs_inserts.script

```

isql -Usa -Pjc4251 -e <<!
use faultdb1
go

drop proc fs_inserts
go

/*****
** Create the STATS stored procedure
*****/

CREATE procedure fs_inserts
(
    @db_name varchar(30),
    @segment_name varchar(30),
    @space_left int,
    @status int
)
as

/*****
** count the number of traps and alarms inserted during the last
** hour.
*****/

DECLARE @alarmRows int
DECLARE @trapRows int
DECLARE @timeStamp varchar(40)
DECLARE @dateStamp varchar(40)

SELECT @timeStamp = (dateadd(hour, -1, getdate()))
SELECT @dateStamp = (getdate())

SELECT @alarmRows = (SELECT count(*) from Alarm where
    TimeStamp > @timeStamp)

SELECT @trapRows = (SELECT count(*) from Trap where
    TimeStamp > @timeStamp)

PRINT "Insert %1!      Alarms since %2! (%3!)",
    @alarmRows, @timeStamp, @dateStamp
PRINT "Insert %1!      Traps since %2! (%3!)",
    @trapRows, @timeStamp, @dateStamp

go
!
```

APPENDIX C

fs_stats.script

```

isql -Usa -Pjc4251 -e <<!
use faultdb1
go

drop proc fs_stats
go

/*****
** Create the STATS stored procedure
*****/

CREATE procedure fs_stats
(
    @db_name varchar(30),
    @segment_name varchar(30),
    @space_left int,
    @status int
)
as

/*****
** purge procedure will now run every hour to avoid LONG
** lockups at midnight. Just in case we have an extremely busy
** hour, limit row count to 45k (15 traps/sec) to avoid running out
** of locks
*****/

DECLARE @alarmRows int
DECLARE @trapRows int
DECLARE @timeStamp varchar(40)
DECLARE @dateStamp varchar(40)

SELECT @timeStamp = (dateadd(day, -1, getdate()))
SELECT @dateStamp = (getdate())

SELECT @alarmRows = (SELECT count(*) from Alarm where
    TimeStamp < dateadd(day, -1, getdate()))

SELECT @trapRows = (SELECT count(*) from Trap where
    TimeStamp < dateadd(day, -1, getdate()))

PRINT "%1!    Alarms older than %2!    (%3!)",
    @alarmRows, @timeStamp, @dateStamp
PRINT "%1!    Traps older than %2!    (%3!)",
    @trapRows, @timeStamp, @dateStamp

SELECT @alarmRows = (SELECT count(*) from Alarm)

SELECT @trapRows = (SELECT count(*) from Trap)

PRINT "%1!    Total Alarms    (%2!)", @alarmRows, @dateStamp
PRINT "%1!    Total Traps    (%2!)", @trapRows, @dateStamp

go
!

```

APPENDIX D

fs_stats_hr.script

```

isql -Usa -Pjc4251 -e <<!
use faultdb1
go

drop proc fs_stats_hr
go

/*****
** Create the STATS stored procedure
*****/
CREATE procedure fs_stats_hr
(
    @db_name varchar(30),
    @segment_name varchar(30),
    @space_left int,
    @status int
)
as
/*****
** purge procedure will now run every hour to avoid LONG lockups at midnight. Just in case we have an
** extremely busy hour, limit row count to 45k (15 traps/sec) to avoid running out of locks
*****/
    DECLARE @alarmRows int
    DECLARE @trapRows int
    DECLARE @timeStamp varchar(40)
    DECLARE @dateStamp varchar(40)
    DECLARE @activeAlarmRetainDays int
    DECLARE @closedAlarmRetainDays int

    SELECT @dateStamp = (getdate())

    SELECT @activeAlarmRetainDays = (SELECT ActiveAlarmRetainDays
    FROM FaultServerConfig)

    SELECT @closedAlarmRetainDays = (SELECT ClosedAlarmRetainDays
    FROM FaultServerConfig)

    SELECT @timeStamp = (dateadd(day, -@activeAlarmRetainDays, getdate()))

    PRINT "activeAlarmRetainDays %1!", @activeAlarmRetainDays
    PRINT "closedAlarmRetainDays %1!", @closedAlarmRetainDays

    SELECT @alarmRows = (SELECT count(*) from Alarm where
    TimeStamp < dateadd(day, -@closedAlarmRetainDays, getdate()))

    SELECT @trapRows = (SELECT count(*) from Trap where
    TimeStamp < dateadd(day, -@closedAlarmRetainDays, getdate()))

    PRINT "Delete %1!      Alarms before %2! (%3!)",
    @alarmRows, @timeStamp, @dateStamp
    PRINT "Delete %1!      Traps before %2! (%3!)",
    @trapRows, @timeStamp, @dateStamp

go
!

```

APPENDIX E

fault_cron

```

#!/bin/ksh

Uname=`uname -n`

reset_all()
{
    export cnt_TrapForw cnt_RuleHand cnt_Reliable cnt_DBIHand cnt_fstrapd
    export cnt_Notifica cnt_AlarmHan cnt_ControlI cnt_AlarmFor cnt_EventHan

    cnt_TrapForw=0
    cnt_RuleHand=0
    cnt_Reliable=0
    cnt_DBIHand=0
    cnt_fstrapd=0
    cnt_Notifica=0
    cnt_AlarmHan=0
    cnt_ControlI=0
    cnt_AlarmFor=0
    cnt_EventHan=0
}

start_it()
{
    cnt=0
    export cnt

    Date=`date +%b %e %T`

    /etc/rc3.d/S99jws stop
    echo "$Date $Uname fault_cron: /etc/rc3.d/S99jws stop" \
        >>/var/adm/messages

    while true
    do
        if ps -fe | grep -i web | grep -v grep
        then
            cnt=`expr $cnt + 1`

            if test $cnt -gt 5
            then
                for x in `ps -fe | grep -i web | \
                    grep -v grep | awk '{print $2}'`
                do
                    kill $x
                done
                break
            fi
            sleep 2
            continue
        fi
        break
    done

    /etc/rc3.d/S77fsd stop

```

```

sleep 2
cd /opt/RelyENT/bin/
/opt/RelyENT/bin/StopAgt.sh

echo "$Date $Uname fault_cron: /etc/rc3.d/S77fsd stop" \
    >>/var/adm/messages

while true
do
    if ps -fe | grep -i cvFault | grep -v grep
    then
        cnt=`expr $cnt + 1`

        if test $cnt -gt 5
        then
            for x in `ps -fe | grep -i cvFault | \
                grep -v grep | awk '{print $2}'`
            do
                Process=`ps -e|grep " $x "|awk '{print $4}'`
                echo "$Date $Uname fault_cron: killing $Process" \
                    >>/var/adm/messages
                kill -9 $x
            done
            break
        fi
        sleep 2
        continue
    fi
    break
done

/etc/rc3.d/S77fsd start
echo "$Date $Uname fault_cron: /etc/rc3.d/S77fsd start" \
    >>/var/adm/messages

sleep 4

/etc/rc3.d/S99jws start
sleep 2
/opt/RelyENT/bin/StartAgt.sh
echo "$Date $Uname fault_cron: /etc/rc3.d/S99jws start" \
    >>/var/adm/messages

reset_all
sleep 2
}

String="RuleHan|DBIdHan|EventHa|AlarmHa|TrapForw|Reliabl|fstra|RuleHa|Notific|Contro|AlarmF"

Date=`date +%b %e %T`
echo "$Date $Uname fault_cron: Starting" >>/var/adm/messages
reset_all

while true
do

    ps -e|egrep "$String" | awk '{print $4}' >/tmp/res.$$
    Date=`date +%b %e %T`

```



```

##for x in TrapForw RuleHand Reliable DBIdHand fstrapd Notifica \
##for x in TrapForw RuleHand Reliable DBIdHand fstrapd Notifica \
    ##AlarmHan Controll AlarmFor EventHan

for x in TrapForw RuleHand DBIdHand fstrapd Notifica \
    AlarmHan AlarmFor EventHan
do
    if grep $x /tmp/res.$$ >/dev/null
    then
        :
    else
        case $x in
            TrapForw) cnt_TrapForw=`expr $cnt_TrapForw + 1`
                echo "$Date $Uname fault_cron: $x stopped $cnt_TrapForw" \
                    >>/var/adm/messages ;;
            RuleHand) cnt_RuleHand=`expr $cnt_RuleHand + 1`
                echo "$Date $Uname fault_cron: $x stopped $cnt_RuleHand" \
                    >>/var/adm/messages ;;
            Reliable) cnt_Reliable=`expr $cnt_Reliable + 1`
                echo "$Date $Uname fault_cron: $x stopped $cnt_Reliable" \
                    >>/var/adm/messages ;;
            DBIdHand) cnt_DBIdHand=`expr $cnt_DBIdHand + 1`
                echo "$Date $Uname fault_cron: $x stopped $cnt_DBIdHand" \
                    >>/var/adm/messages ;;
            fstrapd) cnt_fstrapd=`expr $cnt_fstrapd + 1` ;
                echo "$Date $Uname fault_cron: $x stopped $cnt_fstrapd" \
                    >>/var/adm/messages ;;
            Notifica) cnt_Notifica=`expr $cnt_Notifica + 1`
                echo "$Date $Uname fault_cron: $x stopped $cnt_Notifica" \
                    >>/var/adm/messages ;;
            AlarmHan) cnt_AlarmHan=`expr $cnt_AlarmHan + 1`
                echo "$Date $Uname fault_cron: $x stopped $cnt_AlarmHan" \
                    >>/var/adm/messages ;;
            Controll) cnt_ControlI=`expr $cnt_ControlI + 1`
                echo "$Date $Uname fault_cron: $x stopped $cnt_ControlI" \
                    >>/var/adm/messages ;;
            AlarmFor) cnt_AlarmFor=`expr $cnt_AlarmFor + 1`
                echo "$Date $Uname fault_cron: $x stopped $cnt_AlarmFor" \
                    >>/var/adm/messages ;;
            EventHan) cnt_EventHan=`expr $cnt_EventHan + 1`
                echo "$Date $Uname fault_cron: $x stopped $cnt_EventHan" \
                    >>/var/adm/messages ;;
        esac
    fi
done

if test $cnt_TrapForw -ge 10
then
    start_it
elif test $cnt_RuleHand -ge 10
then
    start_it
elif test $cnt_Reliable -ge 10
then
    start_it
elif test $cnt_DBIdHand -ge 10
then
    start_it
elif test $cnt_fstrapd -ge 10

```

```
then
    start_it
elif test $cnt_Notifica -ge 10
then
    start_it
elif test $cnt_AlarmHan -ge 10
then
    start_it
elif test $cnt_ControlI -ge 10
then
    start_it
elif test $cnt_AlarmFor -ge 10
then
    start_it
elif test $cnt_EventHan -ge 10
then
    start_it
else
    sleep 2
fi
done
rm -f /tmp/res.$$
```

APPENDIX F

check_inserts.sh

```

Uname=`uname -n`
Prog=`basename $0`
PURGELOG=/opt/cvFaultServer/log/fsPurge.log
CHECKLOG=/opt/cvFaultServer/log/check_insert.log
STARS="*****"

Date=`date +%b %e %Y %l:%p|sed 's/ / /g'`

Alarmcnt=`grep "^Insert " $PURGELOG | tail -2 | grep Alarm | wc -l`
nbrAlarms=`grep "^Insert " $PURGELOG | \
    tail -2 | grep Alarm | awk '{print $2}'`

Alarmdate=`grep "^Insert " $PURGELOG | \
    tail -2 | grep Alarm | awk '{print $9,$10,$11,$12}' | \
    sed 's/[()]/g' | sed 's/:./:/`

Trapcnt=`grep "^Insert " $PURGELOG | tail -2 | grep Trap | wc -l`
nbrTraps=`grep "^Insert " $PURGELOG | \
    tail -2 | grep Trap | awk '{print $2}'`

Trapdate=`grep "^Insert " $PURGELOG | \
    tail -2 | grep Trap | awk '{print $9,$10,$11,$12}' | \
    sed 's/[()]/g' | sed 's/:./:/`

if test $Alarmcnt != 1 -a $Trapcnt != 1
then
    echo "fs_inserts not running" >>$CHECKLOG
    exit 1
fi

if test "$Alarmdate" != "$Date" -a "$Trapdate" != "$Date"
then
    echo "date mismatch" >>$CHECKLOG
    exit 1
fi

if test $nbrAlarms -eq 0 -a $nbrTraps -eq 0
then
    echo "`date +%b %e %T` $Uname $Prog: Alarms and Traps have stopped" \
        >>$PURGELOG
    echo "$STARS$STARS$STARS" >>$PURGELOG

    echo "`date +%b %e %T` $Uname $Prog: Alarms and Traps have stopped" \
        >>$CHECKLOG
    echo "$STARS$STARS$STARS" >>$CHECKLOG

    /usr/local/bin/rmcore

    fault_cron=`ps -fe | grep fault_cron | egrep -v "grep" | \
        awk '{print $2}'`

    if test X"$fault_cron" != X
    then
        echo "`date +%b %e %T` $Uname $Prog: kill fault_cron\t$fault_cron" \
            >>$CHECKLOG
    fi

```

```

        kill -9 $fault_cron
    fi

    cnt=0
    while true
    do
        if test $cnt -gt 2
        then
            break
        fi

        fault_cron=`ps -fe | grep fault_cron | egrep -v "grep" | \
            awk '{print $2}'`

        if test X"$fault_cron" != X
        then
            echo "`date +%b %e %T` $Uname $Prog: kill fault_cron\t$fault_cron" \
                >>$CHECKLOG
            kill -9 $fault_cron
            break
        fi
        cnt=`expr $cnt + 1`
        sleep 4
    done

    cnt=0
    export cnt

    Date=`date +%b %e %T`

    echo "$Date $Uname $Prog: /etc/rc3.d/S99jws stop" >>$CHECKLOG
    /etc/rc3.d/S99jws stop >>$CHECKLOG 2>&1

    while true
    do
        if ps -fe | grep -i web | grep -v grep
        then
            cnt=`expr $cnt + 1`

            if test $cnt -gt 5
            then
                for x in `ps -fe | grep -i web | \
                    grep -v grep | awk '{print $2}'`
                do
                    if test X"$x" != X
                    then
                        Process=`ps -e | grep " $x " | awk '{print $4}'`
                        echo "`date +%b %e %T` $Uname $Prog: kill $Process\t$x" \
                            >>$CHECKLOG
                        kill -9 $x
                    fi
                done
                break
            fi
            sleep 5
            continue
        fi
        break
    done

```

```

echo "$Date $Uname $Prog: /etc/rc3.d/S77fsd stop" \
    >>$CHECKLOG
/etc/rc3.d/S77fsd stop >>$CHECKLOG 2>&1

while true
do
    if ps -fe | grep -i cvFault | grep -v grep
    then
        cnt=`expr $cnt + 1`

        if test $cnt -gt 5
        then
            for x in `ps -fe | grep -i cvFault | \
                egrep -v "fsPurge|check_insert|grep" | awk '{print $2}'`
            do
                if test X"$x" != X
                then
                    Process=`ps -e | grep " $x " | awk '{print $4}'`
                    echo "`date +%b %e %T` $Uname $Prog: kill $Process\t$x" \
                        >>$CHECKLOG
                    kill -9 $x
                fi
            done
            break
        fi
        sleep 5
        continue
    fi
    break
done

echo "$Date $Uname $Prog: /etc/rc3.d/S77fsd start" \
    >>$CHECKLOG
/etc/rc3.d/S77fsd start >>$CHECKLOG 2>&1

sleep 4

echo "$Date $Uname $Prog: /etc/rc3.d/S99jws start" \
    >>$CHECKLOG
/etc/rc3.d/S99jws start >>$CHECKLOG 2>&1

echo "$Date $Uname $Prog: Starting fault_cron" \
    >>$CHECKLOG
/usr/local/bin/fault_cron &

echo "$Date $Uname $Prog: Restart complete" \
    >>$CHECKLOG
echo "$STARS$STARS*****" \
    >>$CHECKLOG

else
    echo "Okydoky" >>$PURGELOG
    echo "Okydoky" >>$CHECKLOG
fi

```

APPENDIX G

fspurge.sh

```

#!/bin/sh
# Filename: fsPurge.sh
# Description:
# script to invoke a sybase store procedure to purge the faultdb.
#####

USAGE='Usage: fsPurge.sh server db_name username password sybasePath'
Uname=`uname -n`
Prog=`basename $0`

#####
# check command line arguments
#####
if [ $# -ne 5 ]
then
    echo $USAGE
    exit 1
fi

#####
# log all outputs from isql statements
#####
exec >>/opt/cvFaultServer/log/fsPurge.log 2>&1

SYBASE=$5
export SYBASE
DSQUERY=$1
export DSQUERY
BIN=/opt/cvFaultServer/bin
LOCAL=/usr/local/bin
LOG=/opt/cvFaultServer/log

echo "`date +%b %e %T` $Uname $Prog: Started"
echo "*****\n"

#####
# check and make sure fsPurge.sh is not already running !
#####
ps -e | grep fsPurge.
cnt=`ps -e | grep fsPurge. | wc -l`

if test $cnt -ge 2
then
    echo "`date +%b %e %T` $Uname $Prog: already running"
    exit 1
fi

#####
# The grep will remove output lines that contain a number surrounded by
# any amount of whitespace. If the number is bounded by words, then it
# will not be removed from the output stream.
#####

Status=0; export Status
Count=0

```

```
#####
# test for successful conclusion, i.e. no deadlock, for up to
# 10 times (10 minutes) !
#####

$5/bin/isql -U$3 -P$4 2>&1 <<! | egrep -v -f $BIN/exclude

use $2
go

exec fs_stats_hr $2, "", 0, 0
go
!

while true
do

echo "`n`date +%b %e %T` $Uname $Prog:"
echo "*****"

$5/bin/isql -U$3 -P$4 2>&1 <<! | egrep -v -f $BIN/exclude

use $2
go

exec fs_purgen $2, "", 0, 0
go

!
    Status=`tail /opt/cvFaultServer/log/fsPurge.log | \
        grep "(return status" | tail -1`

    #####
    # did purge succeed ??
    #####
    if test X"$Status" = X"(return status = 0)"
    then
        sleep 5
        break
    fi

    Count=`expr $Count + 1`

    #####
    # try up to 10 more times
    #####
    if test $Count -ge 10
    then
        echo "Purge failed at `date +%b %e %T`"
        sleep 5
        break
    fi

    sleep 60
done

echo "`n`date +%b %e %T` $Uname $Prog:"
echo "*****"
```

```
$5/bin/isql -U$3 -P$4 <<! | egrep -v -f $BIN/exclude

sp_helpdb $2
go
!

echo "\n`date +%b %e %T` $Uname $Prog"
echo "*****"

$5/bin/isql -U$3 -P$4 <<! | egrep -v -f $BIN/exclude

use $2
go

exec fs_inserts $2, "", 0, 0
go
!

nohup $LOCAL/check_inserts.sh >>/opt/cvFaultServer/log/check_insert.log 2>&1 &

echo "\n`date +%b %e %T` $Uname $Prog: Completed"
echo "*****"

if test -f $LOG/DBId*
then
    df -k /opt
    rm -f $LOG/*Buffer*
    df -k /opt
    echo
fi
```